

ASG FINE GROUT



DESCRIPTION

ASG FINE GROUT is a cement-based grout suitable for grouting or pointing joints between Ceramic Floor & Wall Tiles, Vitrified Homogeneous Tiles, Porcelain Tiles, Mosaics, Terracotta, Marbles, Granites etc. Suitable for use at floor and wall, interior or exterior areas. The set grout is durable, compressible and good bonding strength.

PRODUCT DESCRIPTION & SPECIFICATION

COLOUR	White / Grey
SHELF LIFE	12 months
JOINT WIDTH	Up to 3mm wide
SETTING TIME	24 hours
STORAGE	Cool dry location ; Allow free flow of air ; stack on pallet
PACKAGING	20 KG / 25 KG

APPLICATION INSTRUCTION

- During tiling allocate minimum joints of 2mm wide for wall tiling & 3mm wide for floor tiling.
- Allow adhesive bed to set 24 hours before grouting commences.
- Ensure that joints are dry, clean or free of contaminants.
- Apply grout into joints using a grout float / rubber squeegee, ensuring joints are fully compacted with grouting mortar.
- Allow grout to set for minimum 24 hours.
- Allow setting for 24 hours; before grouting commences.

STORAGE

Store in dry and cool condition between 5°C to 30°C



Lot 8600, Batu11, Jalan Segenting, Telok Panglima Garang, 42500 Selangor.

Tel: 603- 3122 8505/8515 Fax: 603- 3122 9505 HP: 6012- 3315160

Email: info@asgplaster.com
<https://www.asgplaster.com>